

# LU05.S02 - Directives

ZipFile with the HTML code-solution

## Hints

- You can download the file and copy the content into the code area of the W3School on the left hand side of the coding window.
- You can execute the code by pressing the *run* button
- The result will be presented in the right hand side of the window.

Your result is supposed to look like displayed in the following image:

```
<!DOCTYPE html>
<html>
<head>
<title>My first Vue page</title>
<style>
div {
margin: 10px;
padding: 10px;
border: solid black 1px;
display: inline-block;
}
.pinkBG{
background-color: lightpink;
}
.blueBG{
background-color: lightblue;
}
.orangeBG{
background-color: lightblue;
color:#FF8000; /* Farbe orange */
font-size:28pt; /* Größe 28pt */
font-family:arial
}
</style>
</head>
<body>
<h1>'v-bind' Example</h1>
<p>The browser finds the class name inside the Vue instance.</p>
<div id="app">
<div v-bind:class="vueClass">this element is bound to the "pinkBG" class.</div>
</div>
<script src="https://unpkg.com/vue@3/dist/vue.global.js"></script>
<script>
const app = Vue.createApp({
data() {
return {
vueClass: "orangeBG"
}
}
})
app.mount('#app')
```



From: <https://wiki.bzz.ch/> - **BZZ - Modulwiki**

Permanent link: <https://wiki.bzz.ch/en/modul/m291/learningunits/lu05/loesungen/02?rev=1737620347>

Last update: **2025/01/23 09:19**

