

# LU05.S02 - VUE Directives warm up

ZipFile with the HTML code-solution

## Hints

- You can download the file and copy the content into the code area of the W3School on the left hand side of the coding window.
- You can execute the code by pressing the *run* button
- The result will be presented in the right hand side of the window.

## Assignments

### 1. box-colour change

1. Test the given script
2. Create a new CSS-Class **blueBG** in analogy to **pinkBG**. Make sure to belabour the DIVs within the script part as well.
3. Execute your script by clicking the *run-Button*.
4. Toggle for testing purpose within your VUE-APP (in the script part) between the blue and pink.

### 2. extended CSS

1. create another css-class *.extended*
2. redefine the bgColor
3. add additional values for color, font-size, font-family, ...
4. Bind this new css-class *.extended* into the HTML-Dom (script-part)
5. Execute your script by having it *run*.

### 3. Save the results

1. Comment your results as you find fit within the html-comment area
2. Save your solution within W3-Save-Area.
  - Therefore you might need a W3-School-Account.
  - Be advised to name you script accordingly, i.e. *lu.s02*. This will be helpful while preparing for the exams.

## Solutions

Your result is supposed to look like displayed in the following image:

```
<!DOCTYPE html>
<html>
<head>
  <title>My first Vue page</title>
  <style>
    div {
      margin: 10px;
      padding: 10px;
      border: solid black 1px;
      display: inline-block;
    }

    .pinkBG{
      background-color: lightpink;
    }

    .blueBG{
      background-color: lightblue;
    }

    .extended{
      background-color: lightblue;
      color: #ff9f00; /* Farbe orange */
      font-size: 28pt; /* Größe 28pt */
      font-family: arial;
    }
  </style>
</head>
<body>

<h1>'v-bind' Example</h1>

<p>The browser finds the class name inside the Vue instance.</p>

<div id="app">
  <p>Everything inside the div element with id="app" can use data from the Vue instance.</p>
  <div v-bind:class="vueClass">This element is bound to the "pinkBG" class.</div>
</div>
<script src="https://unpkg.com/vue@3/dist/vue.global.js"></script>

<script>
const app = Vue.createApp({
  data() {
    return {
      vueClass: "extended"
    }
  }
})
app.mount('#app')
```

### 'v-bind' Example

The browser finds the class name inside the Vue instance.  
Everything inside the div element with id="app" can use data from the Vue instance.

This element is bound to the "pinkBG" class.



Volkan Demir

From:  
<https://wiki.bzz.ch/> - **BZZ - Modulwiki**

Permanent link:  
<https://wiki.bzz.ch/en/modul/m291/learningunits/lu05/loesungen/02?rev=1743151051>

Last update: **2025/03/28 09:37**

