

LU05.S12 - v-show simple applied to texts

Hints

- Download the file and copy the content into the code area of the W3School on the left hand side of the coding window.
- You can execute the code by pressing the *run* button
- The result will be presented in the right hand side of the window.

Assignment

Using the v-show directive by manipulate the value of the showDiv.

Codesolution of v-show simple

The screenshot shows a code editor on the left and a browser window on the right. The code in the editor is as follows:

```

<head>
  <title>v-show</title>
  <style>
    <style>
      border: 1px dashed black;
      width: 200px;
      padding: 5px 20px 20px;
    }
    <div id="app">
      <div v-show="showDiv">This div tag can be hidden</div>
    </div>
  </style>
</head>
<body>
  <div id="app">
    <div v-show="showDiv">This div tag can be hidden</div>
  </div>
</body>
</html>
</script>
<script src="https://unpkg.com/vue@3/dist/vue.global.js"></script>
<script>
  const app = Vue.createApp({
    data() {
      return {
        showDiv: 0
      }
    }
  })
  app.mount('#app')
</script>

```

The browser's developer tools show the rendered HTML structure. The hidden div is highlighted with a red box, showing its style: `display: none;`. A tooltip in the browser explains the 'showDiv' data property.



Volkan Demir

From: <https://wiki.bzz.ch/> - **BZZ - Modulwiki**

Permanent link: <https://wiki.bzz.ch/en/modul/m291/learningunits/lu05/loesungen/13?rev=1742280244>

Last update: 2025/03/18 07:44

