

LU05d - v-show - TBD

Learning objectives

1.

Introduction

The `v-show` directive in Vue.js is used to conditionally display elements based on a boolean expression. *Unlike `v-if`, which completely removes elements from the DOM when the condition is false, `v-show` toggles the CSS display property, keeping the element in the DOM but hiding it visually. This makes `v-show` more efficient when elements need to be frequently shown or hidden without re-rendering. It is best suited for UI toggles, such as modals, dropdowns, or tooltips.*

The syntax is simple:

```
<div v-show="isVisible">Content</div>
```

, where `isVisible` controls the visibility of the element dynamically

Example

```
<template>
  <div>
    <button @click="isVisible = !isVisible">
      Toggle Message
    </button>
    <p v-show="isVisible">Hello, Vue.js!</p>
  </div>
</template>
```

```
<script>
  export default {
    data() {
      return {
        isVisible: true
      };
    }
  };
</script>
```

Explanation: The `v-show="„isVisible“` directive controls the visibility of the `<p>` element.

- Clicking the button toggles `isVisible` between `true` and `false`.
- Instead of removing the element from the DOM, Vue modifies its display property.

Vocabulary

English	German
conditionally	bedingt



Volkan Demir

From:

<https://wiki.bzz.ch/> - **BZZ - Modulwiki**

Permanent link:

<https://wiki.bzz.ch/en/modul/m291/learningunits/lu05/theorie/04?rev=1741952065>

Last update: **2025/03/14 12:34**

