

LU05e - v-for

Learning objectives

1. I can explain what function v-for directives fulfil within the DOM. 2. I can explain which data types v-for is suitable for. 3. I can name the list display variants that are possible with v-for.

Source

[W3School v-for](#)

Introduction

The **v-for** directive in Vue.js is a powerful tool for rendering (the process of converting data, code or digital instructions into a visual representation on the screen) lists of elements in HTML templates. It allows developers to iterate through a data source and create a template element for each element in the data source (e.g. array). In addition to basic lists, **v-for** can also be used to iterate (loop through) a series of numbers, object properties or even nested structures. By combining it with other directives such as **v-bind** and **v-on**, **v-for** extends the possibilities of interactive data binding in Vue applications.

```
<template>
  <ul>
    <li v-for="(item, index) in items" :key="index">
      {{ index + 1 }}. {{ item }}
    </li>
  </ul>
</template>
```

```
<script>
export default {
  data() {
    return {
      items: ["Apple", "Banana", "Cherry"]
    };
  }
};
</script>
```

Explanation

- The `v-for=",(item, index) in items"` directive loops through the `items` array.
- `:key="index"` helps Vue track each element efficiently.
- The output will be a list displaying „Apple,“ „Banana,“ and „Cherry“ in order.

Vocabulary

English	German
to render	ausgeben (Listen)
to iterate	wiederholen, durchlaufen



Volkan Demir

From:

<https://wiki.bzz.ch/> - **BZZ - Modulwiki**

Permanent link:

<https://wiki.bzz.ch/en/modul/m291/learningunits/lu05/theorie/05?rev=1742563627>

Last update: **2025/03/21 14:27**

