

LU07.A03 - Events - TBD

Assignment 1: Preparatory work

- ...

Solution

Methods with several arguments

In this example we see that it is possible to send both the event object and a text as an argument with a method. To do this we must use the reserved name for event methods: 'Sevent'.

Click on the image of the animals above, gto get a proper response:

The code editor shows the following structure:

```

<html lang="en"> Show component usages
<body>
<div id="app">
    <!-- clickin the image triggers the call of the method with the arguments event, greeting, oppinion -->
    <br>
    
    <br>
    
    <br>
    <p id="green">"{{ msgAndId }}</p>
</div>

<script src="https://unpkg.com/vue@3/dist/vue.global.js"></script>
<script>
    const app = Vue.createApp({
        data() {
            return {
                msgAndId: ''
            }
        },
        methods: {
            myMethod(e, msg, opp) { // signature of the method including argument list
                this.msgAndId = msg + ' ' // message to show is built up, step by step
                this.msgAndId += e.target.id + "!"
                this.msgAndId += ' You look ' + opp;
            }
        }
    })
    .mount('#app')
</script>

```

The sidebar on the right contains the following text and images:

In this example we see that it is possible to send both the event object and a text as an argument with a method. To do this we must use the reserved name for event methods: 'Sevent'.

Click on the image of the animals above, gto get a proper response:





"Hello! Lion! You look kingly indeed"

Source-code of the solution

Vocabulary

English	German
...	...



Volkan Demir

From:

<https://wiki.bzz.ch/> - BZZ - Modulwiki

Permanent link:

<https://wiki.bzz.ch/en/modul/m291/learningunits/lu07/loesungen/03?rev=1746432126>

Last update: 2025/05/05 10:02

