

LU06.S03 - SQL-DQL: Selects with Aggregate Functions

A: MIN

We want to know which of our products actually the cheapest is.

```
SELECT min(price)
FROM Products;
```

Result from DB: 2.5

B: MAX

What is the highest price for the products of the supplier with id = 12?

```
SELECT max(price)
FROM Products
WHERE SupplierID = 12;
```

Result from the DB: 123.79

C: AVG

What is the average price for products of supplier 3?

```
SELECT AVG(price)
FROM Products
WHERE SupplierID = 3;
```

Result from the db: 31.6667

D: COUNT

How many orders do we currently have in our data-base system from the customer with id = 5?

```
SELECT count(customerID)
FROM Orders
where customerID = 5;
```

Result from the db: 3

E: SUM

What is the worth of the order 10255? Please note, that there are two tables involved in this select statement.

```
SELECT sum(price*quantity)
FROM OrderDetails, Products
WHERE OrderDetails.OrderID = 10255
AND OrderDetails.ProductID = Products.ProductID;
```

Result from the db: 3115.75

F: GROUP BY

For our annual report we need a list of the orders, and the value of each, grouped by the OrderID.

```
SELECT OrderDetails.orderID, sum(price*quantity)
FROM OrderDetails, Products
WHERE OrderDetails.ProductID = Products.ProductID
GROUP BY OrderDetails.orderid;
```

*** Result from the db:**

```
SELECT OrderDetails.orderID, sum(price*quantity)
FROM OrderDetails, Products
WHERE OrderDetails.ProductID = Products.ProductID
GROUP BY OrderDetails.orderid;
```

Edit the SQL Statement, and click "Run SQL" to see the result.

Run SQL

Result:

Number of Records: 196

orderID	Expr1001
10248	566
10249	2329.25
10250	2267.25
10251	839.5
10252	4662.5
10253	1806
10254	781.5
10255	3115.75

Vocabulary

English	German
...	...



Volkan Demir

From:

<https://wiki.bzz.ch/> - **BZZ - Modulwiki**

Permanent link:

<https://wiki.bzz.ch/modul/m290/learningunits/lu04/loesungen/l03>Last update: **2024/10/17 12:35**