# LU05.S03\_tmp - SQL-DQL: Selects with Aggregate Functions

### **Assignment a: MIN**

We want to know which of our products is actually the most expensive.

```
SELECT max(price)
FROM Products;
```

### **Assignment b: MAX**

What is the lowest price for the products of the supplier with id = 12?

```
SELECT max(price)
FROM Products
WHERE SupplierID = 12;
```

### **Assignment c: AVG**

What is the average price for products of supplier 3?

```
SELECT AVG(price)
FROM Products
WHERE SupplierID = 3;
```

# Assignment d: AVG

How many orders do we currently have in our data-base system from the customer with id = 5?

```
SELECT count(customerID)
FROM Orders
where customerID = 5;
```

## **Assignment e: SUM**

What is the worth of the order 10255? Please note, that there are two tables involved in this select statement.

```
SELECT sum(price*quantity)
FROM OrderDetails, Products
WHERE orderDetails.OrderID = 10255
```

 $up \alpha a te: \\ 2024/09/27 \ modul: \\ m 290: learning units: lu 04: loes ungen: lo 3 https://wiki.bzz.ch/modul/m 290/learning units/lu 04/loes ungen/lo 3? \\ rev = 1727433340$ 12:35

AND OrderDetails.ProductID = Products.ProductID;

# **Assignment f: GROUP BY**

For our anual report we need list of the orders, and the value of each, grouped by the OrderID.

```
SELECT sum(price*quantity)
FROM OrderDetails, Products
WHERE orderDetails.OrderID = 10255
AND OrderDetails.ProductID = Products.ProductID;
```

# **Vocabulary**

English	German



From:

https://wiki.bzz.ch/ - BZZ - Modulwiki

Permanent link:

https://wiki.bzz.ch/modul/m290/learningunits/lu04/loesungen/l03?rev=1727433340

Last update: 2024/09/27 12:35



https://wiki.bzz.ch/ Printed on 2025/10/30 17:54